Pickup Pull Rules

Trucks can pull in Multiple classes if they fall under the rules but can only pull once in each class

Stock Gas Pickup 4x4

- -MUST be 100% street legal
- -NO Added weight
- -MUST have current license and liability insurance
- -MUST pull from factory style hitch or bumper (no pulling style hitch's)
- -Factory style suspension NO blocks or ladder/traction bars, air bags MUST be deflated
- NO headers, Must have full exhaust.
- -NO nitrous/other injections or aftermarket power adders-pro chargers/turbos/superchargers, Factory turbos allowed
- -Programmers/chips ARE legal
- -26" hitch height
- -Rear duals on factory dually trucks only

7000# Hot Street Gas Pickup 4x4

- -Must be 100% street legal
- MUST have current license and liability insurance
- -Front weights Allowed, must be easily removeable by hand, no weight boxes or "tombstones"

Blocks are Legal, but must be easily removable to return to factory suspension /Rear axles cannot be welded to Frame

- Ladder/traction bars and air bags are Legal
- -headers and open exhaust allowed, but must exit under the truck
- -26" hitch height
- -Rear duals on factory dually trucks only

8000# Open Gas Pickup 4x4

- -26" hitch height
- Must be a 4x4 Vehicle, no 2wd

Stock Diesel Pickup 4x4

- -MUST be 100% street legal
- -NO Added weight
- MUST have current license and liability insurance
- -Must pull from a stock receiver hitch-26 inch max height

Must Have the Factory STOCK TURBO AND STOCK INJECTORS

- -No aftermarket power adders -pro charger/superchargers/ twin turbos -unless factory
- -Programmers/chips ARE legal
- -Lift Pumps" fass"/"air dog" Are Legal
- -No blocks, solid or adjustable
- No ladder / traction bars, stock suspension
- Air bags MUST be deflated
- No nitrous, propane or injection of any kind. (Diesel only)
- -No hood stacks
- -Rear duals on factory dually trucks only

8500# Hot Street Diesel Pickup 4x4

- -MUST be 100% street legal
- MUST have current license and liability insurance
- Front weights allowed, must be easily removable by hand, no weight boxes or "tombstones"
- -No water to air intercoolers, air to air only
- Blocks are Legal, must be easily removable by hand to return to factory suspension
- axles cannot be welded to Frame
- Ladder/traction bars and air bags are Legal
- -26" hitch height
- -Rear duals on factory dually trucks only

9500# Open Diesel Pickup 4x4

- -Max hitch height of 26 inches
- -Must be 4x4 vehicle no 2wd